

## **Broadwall Directional Coupler**

Part No:	VT320WC30SKPPC
----------	----------------

1.0	Mechanical Specifications		
1.1	Waveguide type	WR28	
1.1			
	Flange type	FBP320 (Cover) SMA Female	
1.3	Connector type		
1.4	Material	Copper	
1.5	Inside finish	Silver plating	
1.6	Outside finish	Anticorrosion black paint	
1.7	Dimension	L=130 mm	
2.0	Electrical Specifications		
2.1	Frequency range	26.5-40 GHz	
2.2	VSWR (Max)	1.10 (Main line), 1.50 (Secondary line)	
2.3	Coupling	30 ± 0.7 dB	
2.4	Directivity (Min)	30 dB	
3.0	Outline Drawings		
$\frac{4-R^2}{V} \xrightarrow{7.112\pm0.02} 4-\varnothing 3^{+.085}$			



## **Revision History**

Date	Revision	Changes
26-Oct-2006	1	First release

Information furnished is believed to be accurate and reliable. However, Vector Telecom assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of Vector Telecom. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. Vector Telecom products are not authorized for use as critical components in life support devices or systems without express written approval of Vector Telecom.

The Vector Telecom logo is a registered trademark of Vector Telecom Pty Ltd.

© 2006 Vector Telecom Pty Ltd - All rights reserved

Email: sales@vectortele.com

## www.vectortele.com

## Vector Telecom Pty Ltd

Level 40, 140 William Street, Melbourne VIC 3000, Australia Tel: +61 3 9607 8357 - Fax: +61 3 9607 8282 - www.vectortele.com