

Broadwall Directional Coupler

Part No: VT26WC30NKPPA

1.0	No: VT26WC30NKPPA Mechanical Specifications			
1.1	Waveguide Type	WR284		
1.2	Flange Type FDP32 (Cover)			
1.3	Connector Type	N Female		
1.4	Material Aluminum			
1.5	Inside Finish Chromate conversion			
1.6	Outside Finish	Anticorrosion black paint		
1.7	Length	L=890 mm		
2.0	Electrical Specifications			
2.1	Frequency Range	2.6-3.95 GHz		
2.2	VSWR (Max)	1.10 (Main line), 1.25 (Secondary line)		
2.3	Coupling	30 ± 0.7 dB		
2.4	Directivity (Min)	30 dB		
3.0	Outline Drawings			
-	2-FDP32 8	72.5 N-50K 72.5 8		
	4-R6 72.14±0.14 6-Ø6.35**026 72.14**02.14**			



Revision History

Date	Revision	Changes
25-Mar-2009	1	First release

Information furnished is believed to be accurate and reliable. However, Vector Telecom assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of Vector Telecom. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. Vector Telecom products are not authorized for use as critical components in life support devices or systems without express written approval of Vector Telecom.

The Vector Telecom logo is a registered trademark of Vector Telecom Pty Ltd.

© 2006 Vector Telecom Pty Ltd - All rights reserved

Email: sales@vectortele.com

www.vectortele.com