

Waveguide Rotary Joint








Part No: VT120WRJU

1.0	Mechanical Specifications	
1.1	Waveguide type	WR75
1.2	Flange type	FBP120 (Cover)
1.3	Material	Copper
1.4	Inside finish	Silver plating
1.5	Outside finish	Anticorrosion grey paint
1.6	Temperature range	-30°C ~ +70°C
1.7	Style	U style
2.0	Electrical Specifications	
2.1	Frequency range	14-14.5 GHz
2.2	VSWR (Max)	1.20
2.3	VSWR WOW	0.05
2.4	Insertion loss (Max)	0.2 dB
2.5	Insertion loss WOW	0.05 dB
3.0	Outline Drawings	

3.0 Outline Drawings





Revision History

Date	Revision	Changes
09-Mar-2007	1	First release

Information furnished is believed to be accurate and reliable. However, Vector Telecom assumes no responsibility for the consequences of use of such information or for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of Vector Telecom. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. Vector Telecom products are not authorized for use as critical components in life support devices or systems without express written approval of Vector Telecom.

The Vector Telecom logo is a registered trademark of Vector Telecom Pty Ltd.

 $\ @$ 2006 Vector Telecom Pty Ltd - All rights reserved

Email: sales@vectortele.com

www.vectortele.com